

CHAMPION BRAKE FLUID DOT 4 LV

This brake fluid is especially recommended for use in hydraulic brake and clutch systems of vehicles fitted with ESP (Electronic Stability Program) and ABS (Anti-lock Braking System) with a high boiling point and outstanding performance at very low temperatures.

APPLICATIONS

Its high wet boiling point (172°C) is superior to conventional fluids DOT 3 and DOT 4 and therefore enables longer product lifetime. The viscosity at -40 °C of this DOT4 LV is lower than conventional brake fluids allowing an easier fluid circulation in micro-valves of anti-locking systems for better response of ESP, ABS and ASR.

FEATURES

Boiling point: very high boiling point, safe braking.

Anti-corrosion properties: complete brake system protection.

SPECIFICATIONS

FMVSS	116 DOT 4	FORD	WSS-M6C65-A2
FMVSS	116 DOT3	GM	GMW 3356
ISO	4925 Class 3&4	MB	331.0
ISO	4925 Class 6	PSA	S71 2114
SAE	J 1703	TOYOTA	SFU
SAE	J 1704	VW	501 14
BMW	QV 34 001	VW	TL 766-Z
DTFR	308100		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Kinematic viscosity at 100°C	ASTM D445	mm²/s	2.10
pH	ASTM D1287		8.53
Equilibrium Reflux Boiling Point (ERBP)	ASTM D1120	°C	267
Wet Equilibrium Reflux Boiling Point (WERBP)	ASTM D1120	°C	172
Density at 20°C	ASTM D4052	g/ml	1.049
Kinematic viscosity at -40°C	ASTM D445	mm²/s	675

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

