

WOLF ECOTECH CVT-ATF FLUID

15/05/2025
3029

This is a multifunctional full synthetic lubricant that has been designed for both CVT and step automatic transmissions. The multi-vehicle suitability of this oil enables optimized supply chain, reduced operational cost and mitigated misapplication risk.

It offers outstanding anti-wear protection and stable friction characteristics.

APPLICATIONS

It is suitable for continuously variable transmissions (using steel push-belts or chains) and for the latest generation of high efficiency step automatic transmissions where the manufacturer recommends the specifications as referred to in the extensive list on this technical data sheet.

FEATURES

Anti-wear protection: significantly extended transmission life.

Extended oil life: excellent thermal and oxidation stability.

Frictional properties: very smooth gear shifting, no vibration.

SPECIFICATIONS

ACURA	ATF-Z1	CHRYSLER	Dodge/Jeep/ 68043742AA
AIISIN-WARNER	AW-1	DAEWOO	LT 71141
AIISIN-WARNER	AW-2	DAIHATSU	AMIX CVTF DFC
AIISIN-WARNER	JWS 3309(T-IV)	DAIHATSU	AMIX CVTF DFE
AIISIN-WARNER	JWS 3324(W5)	DAIHATSU	AMIX CVTF DTC
ALLISON	C3	DAIHATSU	AMIX CVTF-DC
ALLISON	C4	DAIHATSU	AMMIX ATF D II
AUDI	TL 52180	DAIHATSU	AMMIX ATF D III SP
BMW	83 22 0 136 376	DAIHATSU	FLUID TC
BMW	83 22 2 344 206	DODGE	NS-2/CVTF+4
BMW	83 22 2 344 207	FIAT	T-IV type
BMW	83 22 9 407 765	FORD	CVT23
BMW	ATF 4	FORD	CVT30
BMW	ATF 5	FORD	ESP-M2C166-H
BMW	ATF 6	FORD	FRN 5
BMW	ETL 7045E	FORD	MERCON
BMW	ETL 8072B	FORD	MERCON C
BMW	EZL799/EZL799A	FORD	MERCON SP
BMW	JWS 3309(T-IV)	FORD	WSS-M2C922-A1
BMW	LA 2634	FORD	WSS-M2C924-A
BMW	LT 71141	FORD	WSS-M2C928-A
BMW	ZF 5HP18FL,5HP24,5HP30	FORD	WSS-M2C933-A
BOSCH REXROTH	TE-ML 09	FORD	XT-2 QSM (Syn)
CATERPILLAR	TO-2	FORD	XT-2QDX (M)
CHRYSLER	ATF +, +2, +3	FORD	XT-6-QSP
CHRYSLER	Dodge MOPAR AS 68 RC (T-IV),	FUJIIYUUKO	i-CVTF FG
	JWS 3309	FUSO	ATF -SP III

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



FUSO	ATF-A4	MAZDA	ATF FZ
FUSO	ATF-II	MAZDA	ATF M-III
GEELY	CVTF-EX1	MAZDA	ATF M-V (Type M5)
GM	1940700	MAZDA	ATF N-1
GM	1940767	MAZDA	ATF S-1
GM	21005966	MAZDA	CVTF 3320
GM	22717466	MB	236.20/CVT28
GM	88863400	MINI	EZL799/EZL799A/CVT V1
GM	88863401	MINI	T-IV
GM	88900925	MINI	CVTF ECO J4
GM	93160393	MINI	CVTF J-1
GM	9985010	MINI	CVTF J-4
GM	9985835	MINI	CVTF J-4+
GM	9986195	MINI	Diaqueen ATF PA
GM	AW-1	MINI	Diaqueen AW
GM	CVTF GREEN 2/SATURN DEX-CVT	MINI	Diaqueen J2
GM	DEXRON II	MINI	Diaqueen J3
GM	DEXRON II-D	MINI	Diaqueen SK
GM	DEXRON II-E	MINI	Diaqueen SP
GM	DEXRON III-G	MINI	Diaqueen SP-II
GM	DEXRON III-H	MINI	Diaqueen SP-III
GM	DEXRON TYPE A, SUFFIX A	MINI	Diaqueen SP-IV
HINO	Blue Ribon ATF	MINI	Diaqueen SP-IV
HONDA	ATF Z-1	MINI	Diaqueen SP-IV
HONDA	DW-1	MINI	Diaqueen SP-IV
HONDA	HCF-2/HMMF (No Start Clutch)	MINI	Diaqueen SP-IV
HONDA	Type 3.0 and 3.1	MINI	Diaqueen SP-IV
HONDA	Ultra HEVF-Type 1	MINI	Diaqueen SP-IV
HYUNDAI	040000C90SG	MINI	Diaqueen SP-IV
HYUNDAI	Dex-II/SP-II	MINI	Diaqueen SP-IV
HYUNDAI	SP-CVT1	MINI	Diaqueen SP-IV
HYUNDAI	SP-II M	MINI	Diaqueen SP-IV
HYUNDAI	SP-III	MINI	Diaqueen SP-IV
HYUNDAI	SP-IV M	MINI	Diaqueen SP-IV
HYUNDAI	SP-IV M1	MINI	Diaqueen SP-IV
ISUZU	08200-9001	MINI	Diaqueen SP-IV
ISUZU	BESCO ATF-II	MINI	Diaqueen SP-IV
ISUZU	BESCO ATF-III	MINI	Diaqueen SP-IV
ISUZU	BESCO ATF-SP	MINI	Diaqueen SP-IV
ISUZU	SCS Fluid	MINI	Diaqueen SP-IV
JAGUAR	ATF 3403 JLM 20238	MINI	Diaqueen SP-IV
JAGUAR	ATF 3403 M115	MINI	Diaqueen SP-IV
JAGUAR	JLM 20292	MINI	Diaqueen SP-IV
JAGUAR	LT71141 ZF 5HP24	MINI	Diaqueen SP-IV
JASO	M315-2013 1A	MINI	Diaqueen SP-IV
JASO	M315-2013 1A-LV	MINI	Diaqueen SP-IV
JASO	M315-2013 2A	MINI	Diaqueen SP-IV
JEEP	ATF +3	MINI	Diaqueen SP-IV
JEEP	NS-2/CVTF+4	MINI	Diaqueen SP-IV
KIA	SP-CVT 1	MINI	Diaqueen SP-IV
LEXUS	JWS 3309	MINI	Diaqueen SP-IV
MAZDA	ATF 3317	MINI	Diaqueen SP-IV
MAZDA	ATF A7	MINI	Diaqueen SP-IV
MAZDA	ATF D-II	MINI	Diaqueen SP-IV
MAZDA	ATF F-1	MINI	Diaqueen SP-IV

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



SUBARU	High Torque CVTF	VOLVO	1161521
SUBARU	i-CVTF	VOLVO	1161540/1161640
SUBARU	i-CVTF FG	VOLVO	97325
SUBARU	K0140Y0700	VOLVO	97335
SUBARU	Lineartronic CV-30	VOLVO	CE 97340
SUBARU	Lineartronic CVTF II	VOLVO	CE 97341
SUZUKI	AT OIL 5D06	VOLVO	CVT 4959
SUZUKI	ATF 2326	VW	5HP (18FL, 30)
SUZUKI	ATF 2384K	VW	5HP (19FL, 24A)
SUZUKI	ATF 3314	VW	5HP (ZF 5 HP 30)
SUZUKI	ATF 3317	VW	G 052 025
SUZUKI	ATF AW-1	VW	G 052 055
SUZUKI	ATF JWS 3309	VW	G 052 162
SUZUKI	CVTF 3320	VW	G 052 180
SUZUKI	CVTF 4401	VW	G 052 516
SUZUKI	CVTF GREEN 2	VW	G 052 990
SUZUKI	NS-2/SHELL GREEN 1 V	VW	G 053 001
TOYOTA	ATF D-II	VW	G 053 025
TOYOTA	ATF D-III	VW	G 053 162 A1
TOYOTA	ATF WS	VW	G 055 025
TOYOTA	CVT FE	VW	G 055 540
TOYOTA	TC	VW	TL 52540-A
TOYOTA	TYPE T	ZF	TE-ML 05L
TOYOTA	TYPE T-III	ZF	TE-ML 09X
TOYOTA	TYPE T-IV	ZF	TE-ML 21L

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm²/s	36.5
Kinematic viscosity at 100°C	ASTM D445	mm²/s	7.5
Viscosity index	ASTM D2270		179
Pour point	ASTM D6892	°C	-51
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	15000
Flash Point COC	ASTM D92	°C	190
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.