

# CHAINSAW OIL NON DRIP 72

02/09/2025  
5081

*Sticky and adhesive oil, specifically designed for the lubrication of chain saws. Due to its special composition, it remain in the lubricating area and is not trown out.*

## APPLICATIONS

This oil is mainly applied in chainsaws, but it can also be used on conveyor chains and textile machines, where adhesive oils are required.

## FEATURES

Stickiness: Strong adhesive power

## SPECIFICATIONS

ISO 6743/1

## TYPICAL CHARACTERISTICS

<b>Test</b>	<b>Method</b>	<b>Unit</b>	<b>Average results</b>
Density at 15°C	ASTM D4052	g/ml	0.886
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	145
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	15.5
Viscosity index	ASTM D2270		110
Pour point	ASTM D6892	°C	-30
Flash Point COC	ASTM D92	°C	258

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolfoil.com](http://www.wolfoil.com)

**WOLFOIL**  
CORPORATION