

WOLF OFFICIALTECH 5W30 UHPD FE+

14/04/2025
65649

This full synthetic engine oil is your number one choice to service the most fuel-efficient engines by providing up to 2.2 % increase in fuel economy versus a 15W40 lubricant. It offers complete engine protection thanks to its wear reducing additives, enabling a unique balance between protection and fuel economy. Furthermore, its improved oxidation control and shear stability guarantee maximum fuel economy during the complete oil change interval.

APPLICATIONS

The formulation of this heavy-duty engine oil enables full compatibility with turbochargers, supercharges and after-treatment systems. It offers complete servicing of the most modern and fuel-efficient engines requiring advanced FA-4 engine oils.

It has an official Volvo VDS-5 approval and meets the requirements of the DTFR 15C130 specification (previous MB 228.61).

FEATURES

Fuel economy: superior fuel economy and CO2 reduction.

Total engine protection: outstanding engine cleanliness and durability.

: Aftertreatment protection

SPECIFICATIONS

ACEA	F01
API	approval FA-4/SN
API	SN Plus
JASO	DH-1-17
JASO	DH-2
JASO	DH-2-17
JASO	DL-0-17
CUMMINS	CES 20087
DETROIT DIESEL	DFS 93K223
DTFR	approval 15C130
JASO	DH-2F
MACK	approval EOS-5
RENAULT	approval RLD-5
VOLVO	approval VDS-5

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.856
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	58.5
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	9.9
Viscosity index	ASTM D2270		156
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	9.8
Pour point	ASTM D6892	°C	-33
Sulfated Ash	ASTM D874	Mass %	0.98
Flash Point COC	ASTM D92	°C	220
Colour	VISUAL		DARK BROWN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

