

# WOLF AROW ISO 68

02/03/2026  
4007

A mineral oil, specifically designed to meet the requirements of most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anti-corrosion and anti-foam additives

## APPLICATIONS

This oil is specifically designed to satisfy the requirements of the manufacturers of hydraulic systems where the highest demands are made concerning high pressure, temperatures or speeds. It is recommended for the hydraulic systems of the following types : Vickers, Gerotor, Gresen, HPM, Denison, Cessna, Hydreco and Worthington. It is also suitable for the lubrication of workshop equipment, reducing gears, bearings, compressed air systems and air screw compressors.

## FEATURES

Anti-wear and oxidation stability: superior protection

Anti-foam properties: excellent anti-foam properties

Temperature stability: adequate viscosity stability

## SPECIFICATIONS

|                   |                             |    |           |
|-------------------|-----------------------------|----|-----------|
| AFNOR             | NF E 48-603 HM              | ZF | TE-ML 07H |
| AFNOR             | NF E 48-690                 |    |           |
| AFNOR             | NF E 48-691                 |    |           |
| AGMA              | 9005-E02-RO                 |    |           |
| AIST              | 126 (US Steel)              |    |           |
| AIST              | 127 (US Steel)              |    |           |
| ASTM              | D6158 HL, HM                |    |           |
| CHINESE STANDARD  | GB 11118.1 L-HL, L-HM       |    |           |
| DIN               | 51524 Part 2                |    |           |
| ISO               | 11158, HM                   |    |           |
| ISO               | 20763                       |    |           |
| ISO               | 6743-4, HM                  |    |           |
| JCMAS             | HK P041                     |    |           |
| PARKER (DENISON ) | HF-0, HF-1, HF-2            |    |           |
| SAE               | MS1004                      |    |           |
| SEB               | 181222                      |    |           |
| VICKERS           | I-286-S3                    |    |           |
| BOSCH REXROTH     | approval RDE 90235          |    |           |
| CINCINNATI        | MACHINE P-69 (ISO 68)       |    |           |
| DANIELI           | 0.000.001Rev.15 Typ 10/11   |    |           |
| DENISON           | HF-0, HF-1, HF-2            |    |           |
| EATON VICKERS     | I-286-S                     |    |           |
| EATON VICKERS     | M-2950-S                    |    |           |
| EATON             | Brochure 03-401-2010        |    |           |
| EATON             | E-FDGN-TB002-E              |    |           |
| EATON             | M-2950-S (35VQ25 pump test) |    |           |
| GM                | LS2 AW hyd.oil              |    |           |

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)



## TYPICAL CHARACTERISTICS

| Test                         | Method     | Unit               | Average results |
|------------------------------|------------|--------------------|-----------------|
| Density at 15°C              | ASTM D4052 | g/ml               | 0.884           |
| Kinematic viscosity at 40°C  | ASTM D445  | mm <sup>2</sup> /s | 69              |
| Kinematic viscosity at 100°C | ASTM D445  | mm <sup>2</sup> /s | 8.7             |
| Viscosity index              | ASTM D2270 |                    | 97              |
| Pour point                   | ASTM D6892 | °C                 | -27             |
| Flash Point COC              | ASTM D92   | °C                 | 230             |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolflubes.com](http://www.wolflubes.com)

