

# WOLF OFFICIALTECH GL-4 75W-90 V

20/01/2026  
2319

This is a full synthetic high-performance long drain, severe service manual transmission fluid capable of extending oil drain intervals to 800.000 kilometers.

## APPLICATIONS

This severe service manual transmission fluid can be used in all overdrive Volvo I-shift transmissions and other heavy duty automated manual transmissions.  
Also suitable for Mack mDrive transmissions.

## FEATURES

Anti-wear protection: significantly extended transmission life.  
Extended oil life: excellent thermal and oxidation stability.

Frictional properties: very smooth shift performance.

## SPECIFICATIONS

API	GL-4	MACK	TO-A PLUS
API	MT-1	MB	235.11
ALLISON	TES 439	NAVISTAR	MPAPS B-6816 TYPE 2
ARVIN MERITOR	O-81	VOLVO	97315
DTFR	13B110	VOLVO	97318
EATON	PS-386	VOLVO	97319

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.857
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	103
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	15.7
Viscosity index	ASTM D2270		162
Pour point	ASTM D6892	°C	-45
Flash Point COC	ASTM D92	°C	230

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

