

WOLF ENGINE FLUSH

14/04/2025
70313

Completely cleans the engine interior by eliminating sludge, gum, rust and varnish. Removes carbon deposits, soot, water and unburnt fuel. Reduces fuel consumption and exhaust emissions.

APPLICATIONS

For all gasoline, diesel and LPG engines, with or without turbochargers. Compatible with all mineral and synthetic motor oils. Directions for use : add one bottle to the hot engine oil before changing the oil. Run the engine for 15 minutes and drain the oil. Change the oil filter and refill the engine with an appropriate oil. One bottle treats 3 to 6 liters of engine oil.

FEATURES

-: Complete removal of impurities in the engine

SPECIFICATIONS

/ /

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|---------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.887 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 25.7 |
| B.N. (HClO ₄ method) | ASTM D2896 | mg KOH/g | 4.1 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com