

# WOLF GUARDTECH SAE 50

02/09/2025  
4705

This is a straight mineral oil, made of highly refined base oils.

## APPLICATIONS

Non-detergent engine oil, also for not heavily loaded gearboxes. Lubrication by hand (oilcan). Lubrication of air compressors with low discharge temperatures or when an oil of DIN-VC-class is required.

## FEATURES

Total engine protection: engine protection and cleanliness

## SPECIFICATIONS

API SA

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.895
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	198
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	17.8
Viscosity index	ASTM D2270		98
Pour point	ASTM D6892	°C	-9
Flash Point COC	ASTM D92	°C	270

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

