

WOLF OFFICIALTECH 5W30 C4

29/05/2025
65608

This is a full synthetic lubricant based on carefully selected very high quality base oils, specifically formulated to provide superior protection of the after-treatment systems of Renault engines.

APPLICATIONS

Gasoline and diesel engines of passenger cars with or without turbo which are equipped with a DPF and a TWC (Three-Way Catalyst).

FEATURES

Aftertreatment protection: full aftertreatment system protection
Total engine protection: outstanding engine cleanliness and durability
Fuel economy: lower fuel consumption and CO2 emissions

SPECIFICATIONS

ACEA	C3	MB	approval 226.51
ACEA	C4	MB	approval 229.51
FIAT	9.55535-S4	RENAULT	approval RN 0720
MB	229.31	SUZUKI	SFU

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	67.1
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.8
Viscosity index	ASTM D2270		173
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	6.4
Pour point	ASTM D6892	°C	-39
CCS viscosity at -30°C	ASTM D5293	mPa.s	5800
Sulfated Ash	ASTM D874	Mass %	0.5
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.