

CHAMPION WAY OIL

ISO 220

This oil is particularly used for the lubrication of machine tool slideways. By the use of special additives, the adhesive and lubricity properties are increased and shocks (so-called stick-slip) are avoided.

APPLICATIONS

This oil is specifically suitable for slideways of machine tools, chains, reductions, and general lubrication of machines when oil spattering has to be avoided.

FEATURES

Stick-slip performance: good stick-slip test results

Extreme pressure properties: mild EP properties

SPECIFICATIONS

AFNOR	NF E 48-603 HM	DIN	51524 Part 2
DIN	51502 CGLP	CININNATI	MILACRON P-50

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.894
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	210
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	17.9
Viscosity index	ASTM D2270		93
A.N. [Colorimetric]	ASTM D974	mg KOH/g	0.40
Pour point	ASTM D6892	°C	-18
Flash Point COC	ASTM D92	°C	240

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

