

# WOLF VITALTECH ATF D III PC

14/04/2025  
3009

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This is an oil with a very high viscosity index for most automatic transmissions. The improved fluidity at low temperatures ensures optimum performance in all conditions. Its exceptional frictional characteristics provide smooth switching and driving comfort.

## APPLICATIONS

This oil is used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron III or Dexron II E and Ford Mercon-requirements.

## FEATURES

Frictional properties: smooth shift performance.  
Anti-wear protection: extended transmission life.  
Extended oil life: excellent thermal and oxidation stability.

## SPECIFICATIONS

DTFR	13C120	FORD	MERCON
FORD	ESP-M2C138-CJ	GM	DEXRON III-H
FORD	ESP-M2C166-H	MB	236.2

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.849
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	32.0
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	6.82
Viscosity index	ASTM D2270		181
Pour point	ASTM D6892	°C	-51
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	198
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.