

# WOLF OFFICIALTECH 5W30 C2

14/04/2025  
65610

This is a full synthetic lubricant based on carefully selected very high quality base oils. This high-performance engine oil with low viscosity is specifically developed to provide the highest fuel economy and lowest CO2 emissions.

## APPLICATIONS

Specifically recommended for Peugeot and Citroën gasoline and diesel engines equipped with diesel particulate filters. Most Japanese OEM's, including Toyota, Honda, Subaru and Nissan.

## FEATURES

Aftertreatment protection: full aftertreatment system protection  
Total engine protection: outstanding engine cleanliness and durability  
Fuel economy: lower fuel consumption and CO2 emissions

## SPECIFICATIONS

ACEA	C2	FIAT	9.55535-S1
API	SN/CF	PSA	B71 2290-2014
ILSAC	GF-5	RENAULT	RN 0700

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.856
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	57.0
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	10.1
Viscosity index	ASTM D2270		167
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	7.5
Pour point	ASTM D6892	°C	-39
CCS viscosity at -30°C	ASTM D5293	mPa.s	5500
Sulfated Ash	ASTM D874	Mass %	0.79
Flash Point COC	ASTM D92	°C	232

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

