

# MOTOR OIL SF/CD SAE 50

14/04/2025  
185

*Monograde engine oil for the lubrication of gasoline and diesel engines of passenger cars, with or without turbo. This oil is characterized by a combination of good detergent and dispersant properties, together with a low ash content.*

## APPLICATIONS

This oil is suitable for the lubrication of gasoline and diesel engines from 1980 to 1989.

## FEATURES

Total engine protection: engine protection and cleanliness

## SPECIFICATIONS

API	SF/CD	MB	226.0
MIL	L-46152 B		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.896
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	204
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	17.8
Viscosity index	ASTM D2270		95
B.N. (HClO <sub>4</sub> method)	ASTM D2896	mg KOH/g	5.8
Pour point	ASTM D6892	°C	-24
Flash Point COC	ASTM D92	°C	250

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolfoil.com](http://www.wolfoil.com)

**WOLFOIL**  
CORPORATION