

CHAMPION PROPULSE TT 4T 5W40 ESTER

This ester-based synthetic blend can be used within engines, transmissions and wet clutches. Its groundbreaking additive technology increases both engine performance and protects all lubricated parts completely. This powerful formulation covers a large part of the motorcycle market thanks to its high-end properties. Its great fluidity at low temperatures ensures complete protection of all parts right after starting the engine.

APPLICATIONS

This four-stroke motorcycle engine oil exceeds the standards of API SN, SM, SL and SJ. It surpasses the requirements set by different manufacturers.

FEATURES

*Total engine protection: improved engine, transmission & wet clutch performance.
Riding comfort: recommended product for touring & daily riding
Economic properties: easier fluid management thanks to the oil's broad applicability*

SPECIFICATIONS

API SN JASO approval MA2

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.855 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 85 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 13.8 |
| Viscosity index | ASTM D2270 | | 169 |
| B.N. [HCL04 method] | ASTM D2896 | mg KOH/g | 7.3 |
| Pour point | ASTM D6892 | °C | -42 |
| Colour | VISUAL | | RED |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 3 870 00 00
www.championlubes.com

