

CHAMPION OEM SPECIFIC 15W40 MS EXTRA

Keeping the engine in optimal condition, therefore increasing vehicle uptime, is the core task of this low SAPS oil. It achieves this by offering high wear resistance and complete engine cleanliness, optimising vehicle uptime compared to previous engine oil formulations. The engine oil's high viscosity grade enables this engine oil to maintain its excellent protective properties, even in hot climates and rough conditions.

APPLICATIONS

This versatile product meets the requirements of challenging specifications like the Mack EO-S 4.5, Renault RLD-4 or Volvo VDS-4.5. It is backward compatible with preceding oil categories like CJ-4, suiting the needs of both recent and older engines. It is compatible with emission control technology EURO IV, V and VI for trucks; as well as stage IIIB, IV and Tier 4i, 4f for heavy-duty off-road.

FEATURES

Improved engine cleanliness: increased operating hours

High wear protection: increased engine lifespan

Increased oxidative stability: extended optimal oil performance

SPECIFICATIONS

ACEA	E11	DEUTZ	DQC-III-10 LA
ACEA	E7	DTR	approval 15C100
ACEA	E9-16	FORD	WSS-M2C171-F1
API	CI-4	JD	JDQ-78X
API	CI-4 Plus	MACK	approval EO-S 4.5
API	CJ-4	MACK	EO-M PLUS
API	CK-4/SP	MACK	EO-N
API	SN Plus	MACK	EO-N Premium Plus
CHINESE STANDARD	D1	MACK	EO-O Premium Plus
JASO	DH-2	MAN	approval M3775
AGCO/ALLIS	POWER LOCC-G1	MAN	M3575
ALLISON	C4	MTU	approval Oil Category 2.1
ALLISON	TES 439	RENAULT	approval RLD-3
CASE	MAT 3571	RENAULT	RGD
CASE	MAT 3572	RENAULT	RLD
CATERPILLAR	ECF-1a	RENAULT	RLD-2
CATERPILLAR	ECF-2	RENAULT	RLD-4
CATERPILLAR	ECF-3	RENAULT	RXD
CATERPILLAR	TO-2	VALTRA	S-Series
CUMMINS	CES 20076	VOLVO	approval VDS-4.5
CUMMINS	CES 20077	VOLVO	VDS-3
CUMMINS	CES 20078	VOLVO	VDS-4
CUMMINS	CES 20081		
CUMMINS	CES 20086		
CUMMINS	CES 20100		
DETROIT DIESEL	DFS 93K222		
DEUTZ	approval DQC-III-18 LA		

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION
LUBRICANTS



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.860
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	92.5
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.7
Viscosity index	ASTM D2270		150
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	9.5
Pour point	ASTM D6892	°C	-36
Sulfated Ash	ASTM D874	Mass %	1.0
Flash Point COC	ASTM D92	°C	226

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

