

# ATF DEXRON III

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This is an oil with a very high viscosity index for most automatic transmissions. The improved fluidity at low temperatures ensures optimum performance in all conditions. Its exceptional frictional characteristics provide smooth switching and driving comfort.

## APPLICATIONS

This oil is used in automatic transmissions, torque convertors, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron III or Dexron II E and Ford Mercon-requirements.

## FEATURES

- Frictional properties: smooth shift performance
- Anti-wear protection: extended transmission life
- Extended oil life: excellent thermal and oxidation stability

## PERFORMANCE PROFILE

### SPECIFICATIONS

ALLISON - C4	GM - DEXRON II-D	PSA - 9730 AC	ZF - TE-ML 11B
DTFR - 13C140	GM - DEXRON III-H	VOITH - H55.6335xx	ZF - TE-ML 14A
DTFR - 13C150	MAN - 339 V1/Z1	ZF - TE-ML 03D	ZF - TE-ML 17C
DTFR - 13C170	MB - 236.5	ZF - TE-ML 04D	ZF - TE-ML 21L
FORD - MERCON	MB - 236.6	ZF - TE-ML 05L	
GM - 6417-M DEXRON III-G	MB - 236.93	ZF - TE-ML 09	

## TYPICAL CHARACTERISTICS

TEST	METHOD	UNIT	AVERAGE RESULTS
Density at 15°C	ASTM D4052	g/ml	0.847
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	33.9
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	7.1
Viscosity index	ASTM D2270		179
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	17500
Flash Point COC	ASTM D92	°C	196
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.