

CHAMPION MOTO HP 4T 10W40 SCOOTER

Thanks to its stable mineral and synthetic base oils and the advanced additive package, this four-stroke scooter engine oil guarantees a smooth and stable ride. The balanced formula is developed to exactly suit the needs of scooter enthusiasts looking for optimal riding comfort.

APPLICATIONS

This lubricant is developed for scooter engines. It is perfectly balanced to meet the requirements of several manufacturers.

FEATURES

Engine protection: extended scooter lifespan thanks to the oil's protective properties

Riding comfort: protects the original riding comfort

Applicability: simpler fluid management thanks to the oil's broad applicability

SPECIFICATIONS

API

SL

JASO

MA2

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	90
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	14.0
Viscosity index	ASTM D2270		160
B.N. [HClO4 method]	ASTM D2896	mg KOH/g	6.1
Pour point	ASTM D6892	°C	-36
CCS viscosity at -25°C	ASTM D5293	mPa.s	4900
Colour	VISUAL		BROWN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

