

# CHAMPION MOTO HP 2T SNOWSCOOTER

Thanks to its stable synthetic blend of base oils and advanced additive package, this two-stroke snowscooter engine oil guarantees a smooth and stable ride. The balanced formula is developed to exactly suit the needs of snowscooter enthusiasts looking for optimal riding comfort.

## APPLICATIONS

This lubricant is developed for the engines of 2-stroke snowscooters. Please follow the dosage recommendations of the equipment manufacturer.

## FEATURES

*Engine protection: extended snowscooter lifespan thanks to the oil's protective properties.*

*Riding comfort: protects the original riding comfort*

*Economic properties: simpler fluid management thanks to the oil's broad applicability*

## SPECIFICATIONS

API	TC	NMMA	TC-W3
JASO	FC		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.857
Kinematic viscosity at 40°C	ASTM D445	mm²/s	42.7
Kinematic viscosity at 100°C	ASTM D445	mm²/s	7.9
Viscosity index	ASTM D2270		158
B.N. [HClO4 method]	ASTM D2896	mg KOH/g	5.1
Pour point	ASTM D6892	°C	-42
Flash Point COC	ASTM D92	°C	104
Colour	VISUAL		BLACKISH GREEN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

