

WOLF MOTO 4T 5W50 RACING ESTER

14/04/2025
29168

This synthetic blend motorcycle engine oil contains groundbreaking additive technology and ester-based base oils. This lubricant increases both engine performance and protects all lubricated parts completely. This powerful formulation covers a large part of the motorcycle market thanks to its high-end properties.

APPLICATIONS

This four-stroke motorcycle engine oil exceeds the standards of API SN, SM, SL, SJ, SH and SG. It surpasses the requirements set by different manufacturers.

FEATURES

SPECIFICATIONS

API SN JASO approval MA2

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.850
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	104
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	17.8
Viscosity index	ASTM D2270		189
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	7.3
Pour point	ASTM D6892	°C	-45
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

