

# CHAMPION CENTRAL HYDRAULIC FLUID ASIAN

This central hydraulic fluid is based on carefully selected very high quality base oils and the latest additive technology for the optimum functioning of hydraulic systems.  
It is reliable power transmission fluid, even under difficult conditions, with a high and stable viscosity index

## APPLICATIONS

This CHF is especially developed for the performance requirements of hydraulic systems (power steering) of Asian manufacturers in a wide temperature range.  
Compatible with many common elastomers and sealing materials.

## FEATURES

Pour point: excellent low temperature properties.

## SPECIFICATIONS

<b>ACURA</b>	08206-9002A	<b>MITSUBISHI</b>	DIAMOND SP III
<b>HONDA</b>	08206-9002A	<b>MITSUBISHI</b>	PS FLUID
<b>HONDA</b>	PSF-2	<b>NISSAN</b>	PSF-II
<b>HONDA</b>	PSF-S	<b>PSA</b>	9735 EJ
<b>HONDA</b>	PSF-V	<b>SUBARU</b>	K0209A0080
<b>HYUNDAI</b>	PSF-3	<b>SUBARU</b>	PS FLUID
<b>KIA</b>	PSF-III	<b>TOYOTA</b>	008886-01
<b>MAZDA</b>	PSF	<b>TOYOTA</b>	PSF-EH
<b>MITSUBISHI</b>	DIAMOND PSF-2M		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.870
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	36.3
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	7.5
Viscosity index	ASTM D2270		180
Pour point	ASTM D6892	°C	-52
Flash Point COC	ASTM D92	°C	186
Colour	VISUAL		YELLOW

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

