

WOLF AROWEP ISO 150

02/03/2026
4109

This is an extreme pressure oil for industrial gears. The paraffinic character of the base oil ensures an excellent course of the viscosity/temperature curve and a high resistance against oxidation and ageing. This favorable property of mineral base oil is further strengthened by the addition of appropriate additives. The high pressure additives based on sulfur and phosphorus compounds form a chemical film on tooth surfaces and as such prevents wear and a noticeable reduction in friction. Special anti-corrosion and anti-foam additives complete the composition of this oil.

ZASTOSOWANIA

This oil is recommended for the lubrication of gearboxes (lubrication by oil bath, oil mist or oil circulation) and it is specifically suitable for heavy loads and high temperature.

CECHY

Extreme pressure properties: superior EP properties
Anti-wear and oxidation stability: adequate protection of systems

SPECYFIKACJA

AGMA	9005-E02	ISO	12925-1 CKC
AISE	224	ISO	12925-1 CKD
DIN	51517 CLP	DAVID BROWN	S1.53.101E

TYPOWE CECHY

Test	Metoda	Jednostka	Średni wynik
Gęstość w temp. 15°C	ASTM D4052	g/ml	0.896
Lepkość kinematyczna przy temp. 40°C	ASTM D445	mm ² /s	152
Lepkość kinematyczna w temp. 100°C	ASTM D445	mm ² /s	14.5
Indeks lepkości	ASTM D2270		93
A.N. (kolorymetrycznie)	ASTM D974	mg KOH/g	0.34
Temperatura krzepnięcia	ASTM D6892	°C	-24
Tempera zapłonu metodą Clevelanda	ASTM D92	°C	240
Test F Z G	DIN 51354		12

Zastrzegamy sobie prawo do modyfikowania ogólnych charakterystyk naszych produktów, aby umożliwić naszym klientom czerpanie maksymalnych korzyści z najnowszych odkryć techniki.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

