

CHAMPION OEM LEVEL 5W-30 UHPD

This synthetic based engine oil meets the specifications of a very broad range of different large truck manufacturers. Its low viscosity formulation and advanced friction modifiers allow you to increase fuel efficiency.

APPLICATIONS

This versatile lubricant can be used in a broad range of different EURO V and EURO VI engines. It meets the specifications of different off- and on-road engine manufacturers, such as: Caterpillar, Cummins, DAF, Daimler Truck, Iveco, MAN, Renault, Scania, Volvo, etc.

FEATURES

Low viscosity and excellent friction reduction: increased fuel efficiency
Broad applicability: can be used to service multiple vehicles within one fleet

SPECIFICATIONS

ACEA	E11	MACK	EO-N
ACEA	E6-16	MACK	EO-N Premium Plus
ACEA	E7	MACK	EO-O Premium Plus
ACEA	E8	MACK	EO-S 4.5
ACEA	E9-16	MAN	M3271-1
API	CI-4	MAN	M3277
API	CJ-4	MAN	M3477
API	CK-4	MAN	M3575
API	SN	MAN	M3677
JASO	DH-2	MAN	M3775
CATERPILLAR	ECF-3	MB	235.28
CUMMINS	CES 20077	MTU	Oil Category 2.1
CUMMINS	CES 20081	MTU	Oil Category 3
CUMMINS	CES 20086	MTU	Oil Category 3.1
DAF	EXTENDED DRAIN	RENAULT	RGD
DAF	PSQL 2.1 E	RENAULT	RLD
DAF	PSQL 2.1 E LD	RENAULT	RLD-2
DETROIT DIESEL	DFS 93K218	RENAULT	RLD-3
DETROIT DIESEL	DFS 93K222	RENAULT	RLD-4
DEUTZ	DQC IV-10 LA	RENAULT	RXD
DEUTZ	DQC-IV-10	SCANIA	LDF-3 [excl. V8 engines]
DEUTZ	DQC-IV-18 LA	SCANIA	LDF-4
DEUTZ	TTCD	VOITH	Retarder Oil Class B
DTFR	13D110	VOLVO	VDS-3
DTFR	15C100	VOLVO	VDS-4
DTFR	15C110	VOLVO	VDS-4.5
DTFR	15C120		
FORD	WSS-M2C213-A1		
IVECO	18-1804 Classe TLS E9		
MACK	EO-M PLUS		

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION
LUBRICANTS



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.855
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	74.6
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	12.2
Viscosity index	ASTM D2270		161
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	11.9
Pour point	ASTM D6892	°C	-39
Sulfated Ash	ASTM D874	Mass %	0.99
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

