

WOLF OFFICIALTECH 10W40 UHPD MS

02/03/2026
15708

This is a semi synthetic lubricant based on carefully selected very high quality base oils, which satisfies the highest performance standards for large trucks. It can be used for engines equipped with aftertreatment systems.

APPLICATIONS

Due to its versatile specification levels it is suitable for a wide range of commercial vehicles. Specifically recommended for large truck engines to satisfy the EURO VI standard, TIER IV interim, TIER IV final, TIER V , stage IIIB, stage IV, stage V.

FEATURES

Aftertreatment protection: full after treatment system protection

Total engine protection: outstanding engine cleanliness and durability

SPECIFICATIONS

ACEA	E11	DAF	EXTENDED DRAIN
ACEA	E6-16	DETROIT DIESEL	DFS 93K215
ACEA	E7	DETROIT DIESEL	DFS 93K218
ACEA	E8	DETROIT DIESEL	DFS 93K222
ACEA	E9-16	DEUTZ	approval DQC-IV-18 LA
API	approval CI-4 Plus	DEUTZ	DQC IV-10 LA
API	approval CK-4	DEUTZ	TTCD
API	CI-4	DTFR	13D110
API	CJ-4	DTFR	15C100
API	SN	DTFR	approval 15C110
JASO	DH-1	DTFR	approval 15C120
JASO	DH-2	FORD	WSS-M2C171-F1
AGCO/ALLIS	POWER LOCC-G2	IVECO	18-1804 Classe T2 E7
ALLISON	C4	IVECO	18-1804 Classe TLS E9
CASE	MAT 3571	JD	JDQ-78X
CASE	MAT 3572	LIEBHERR	LH-00-ENG5C LA
CATERPILLAR	ECF-1a	MACK	approval EO-S 4.5
CATERPILLAR	ECF-2	MACK	EO-M PLUS
CATERPILLAR	ECF-3	MACK	EO-N
CATERPILLAR	TO-2	MACK	EO-N Premium Plus
CUMMINS	CES 20076	MACK	EO-O Premium Plus
CUMMINS	CES 20077	MAN	approval M3775
CUMMINS	CES 20078	MAN	M3271-1
CUMMINS	CES 20081	MAN	M3477
CUMMINS	CES 20086	MAN	M3575
CUMMINS	CES 20092	MB	235.28
CUMMINS	CES 20100	MTU	approval Oil Category 3.1

WOLF OIL CORPORATION NV

G. Gillotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



MTU	Oil Category 2.1	RENAULT	RXD
RENAULT	approval RLD-3	SCANIA	LA
RENAULT	RGD	VOITH	Retarder Oil Class B
RENAULT	RLD	VOLVO	approval VDS-4.5
RENAULT	RLD-2	VOLVO	VDS-3
RENAULT	RLD-4	VOLVO	VDS-4

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.858
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	95
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	14.5
Viscosity index	ASTM D2270		158
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	10.2
Pour point	ASTM D6892	°C	-33
CCS viscosity at -25°C	ASTM D5293	mPa.s	6600
Flash Point COC	ASTM D92	°C	216

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.