

WOLF ESSENTIAL

C2/C3 5W-30

03/03/2026
75647

This API SQ engine oil is designed to meet the core requirements of ACEA and API for passenger cars. It offers complete protection of both the aftertreatment system and the engine, regardless the driving conditions. This lubricant may not be available in your region. Please, consult your local sales contact for more information.

APPLICATIONS

Formulated to meet recent OEM specifications. It can be used to service a wide range of EURO 4 and EURO 5-engines of different manufacturers, with or without diesel particulate filter.

FEATURES

Aftertreatment protection: full aftertreatment device protection.

Fuel economy: lower fuel consumption and CO₂ emissions.

Total engine protection: outstanding engine cleanliness and durability.

SPECIFICATIONS

ACEA	C2	MB	229.31
ACEA	C3	MB	229.51
API	SQ	MB	229.52
BMW	LONGLIFE-04	VW	505 00
GM	dexos™2	VW	505 01

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.854
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	74.2
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	12.3
Viscosity index	ASTM D2270		164
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

