

CHAMPION PRORACING GP 4T TRANSMISSION OIL 75W90

This advanced synthetic blend transmission oil for motorcycles has a very high viscosity index. The oil's excellent viscosity at low temperatures guarantees quick protection of all gears.

APPLICATIONS

This is a special transmission oil with extreme pressure properties, specifically composed in order to prevent corrosion on copper alloys. It is compatible with most modern gearboxes and shaft drives.

FEATURES

Excellent friction balance: smooth gear shifts

Powerful protective properties: extended lifespan

Broad material compatibility: fewer fluids required to maintain several motorcycles

SPECIFICATIONS

API GL-5 MIL L-2105 D

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.863
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	70.0
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	14.5
Viscosity index	ASTM D2270		218
Pour point	ASTM D6892	°C	-45
Flash Point COC	ASTM D92	°C	206
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

