

# CHAMPION OEM SPECIFIC OW30 SP

This is a full synthetic lubricant based on carefully selected very high quality base oils. This oil is specifically formulated to meet both the BMW Longlife-12 FE and the Ford WSS M2C950-A specification. It is adapted to meet the requirements of the latest technology, highly engineered turbo engines requiring high performance and lower viscosity oils.

## APPLICATIONS

This product is mandatory in the newest BMW and Ford gasoline and diesel engines. It provides a multi vehicle application through the ACEA C2 specification. Optimum formulation for today's cars with exceptional film strength preventing oil film breakdown and reducing friction providing fuel economy and reliability.

## FEATURES

Total engine protection: performance in keeping the engine clean.

Fuel economy: superior fuel economy and CO2 reduction.

Cold start: excellent fluidity at low temperature.

## SPECIFICATIONS

|                          |                        |                   |           |
|--------------------------|------------------------|-------------------|-----------|
| <b>ACEA</b>              | A5/B5-21               | <b>SSANG YONG</b> | SFU       |
| <b>ACEA</b>              | C2                     | <b>SUZUKI</b>     | SFU       |
| <b>API</b>               | SN Plus                | <b>TOYOTA</b>     | SFU       |
| <b>API</b>               | SP                     | <b>VW</b>         | VWC 53035 |
| <b>API</b>               | SP/RC                  |                   |           |
| <b>ILSAC</b>             | GF-5                   |                   |           |
| <b>ILSAC</b>             | GF-6 A                 |                   |           |
| <b>ALFA ROMEO</b>        | SFU                    |                   |           |
| <b>BMW</b>               | approval LONGLIFE-12FE |                   |           |
| <b>DTFR</b>              | approval 15D100        |                   |           |
| <b>FIAT</b>              | 9.55535-DS1            |                   |           |
| <b>FIAT</b>              | 9.55535-GS1            |                   |           |
| <b>FORD</b>              | WSS-M2C950-A           |                   |           |
| <b>GENESIS</b>           | SFU                    |                   |           |
| <b>HONDA</b>             | SFU                    |                   |           |
| <b>HYUNDAI</b>           | SFU                    |                   |           |
| <b>JAGUAR-LAND ROVER</b> | STJLR.03.5007          |                   |           |
| <b>KIA</b>               | SFU                    |                   |           |
| <b>LANCIA</b>            | SFU                    |                   |           |
| <b>LEXUS</b>             | SFU                    |                   |           |
| <b>MASERATI</b>          | SFU                    |                   |           |
| <b>MB</b>                | 227.61                 |                   |           |
| <b>MB</b>                | approval 229.61        |                   |           |
| <b>MINI</b>              | SFU                    |                   |           |
| <b>MITSUBISHI</b>        | SFU                    |                   |           |
| <b>OPEL</b>              | OV 040 1547 - G30      |                   |           |
| <b>ROLLS-ROYCE</b>       | SFU                    |                   |           |

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)





## TYPICAL CHARACTERISTICS

| Test                         | Method     | Unit               | Average results |
|------------------------------|------------|--------------------|-----------------|
| Density at 15°C              | ASTM D4052 | g/ml               | 0.843           |
| Kinematic viscosity at 40°C  | ASTM D445  | mm <sup>2</sup> /s | 48.3            |
| Kinematic viscosity at 100°C | ASTM D445  | mm <sup>2</sup> /s | 9.8             |
| Viscosity index              | ASTM D2270 |                    | 194             |
| B.N. (HClO4 method)          | ASTM D2896 | mg KOH/g           | 9.4             |
| Pour point                   | ASTM D6892 | °C                 | -48             |
| Flash Point COC              | ASTM D92   | °C                 | 224             |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

