

CHAMPION OEM SPECIFIC 0W-20 C5 P

A low SAPS ACEA C5 passenger car engine oil focused on the most recent Stellantis / PSA specification B71 2010, but also suitable for diesel and gasoline engines from other car manufacturers which require an ACEA C5 SAE 0W-20 oil.

APPLICATIONS

Specifically designed for the most recent PSA GROUP (Peugeot/Citroën/DS) engines which require a PSA B71 2010 oil as Blue HDi, PureTech, hybrid engines, engines equipped with a Stop & Start system, etc. This ACEA C5 oil is also suitable for diesel and gasoline engines from other car manufacturers which require an ACEA C5 SAE 0W-20 oil.

FEATURES

Aftertreatment protection: full aftertreatment device protection.

Cold start: excellent fluidity at low temperature.

Fuel economy: superior fuel economy and CO₂ reduction.

SPECIFICATIONS

ACEA	C5	LEXUS	SFU
API	SN Plus	MAZDA	SFU
API	SP	MB	229.71
ILSAC	GF-5	NISSAN	SFU
ILSAC	GF-6 A	OPEL	OV 040 1547 - A20
CHRYSLER	MS 6395	PERODUA	SFU
FIAT	9.55535-CR1	PSA	approval B71 2010-22
FIAT	9.55535-DM1	ROEWE	SFU
FIAT	9.55535-DSX	SCION	SFU
FIAT	9.55535-GSX	SUBARU	SFU
HONDA	SFU	TATA	SFU
HYUNDAI	SFU	TIANJIN	SFU
INFINITI	SFU	TOYOTA	SFU
KIA	SFU		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.845
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	43.5
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.3
Viscosity index	ASTM D2270		170
Pour point	ASTM D6892	°C	-48
Flash Point COC	ASTM D92	°C	232

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

