

# ATF LIFE PROTECT 8

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6, 8 and 9-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting.

## APPLICATIONS

Exclusively intended for the ZF 6,8 and 9 speed automatic transmissions, as fitted in VW, BMW, Jaguar, Land Rover, Jeep, Chrysler and FIAT group.

## FEATURES

- Anti-wear protection: significantly extended transmission life
- Frictional properties: very smooth gear shifting, no vibration
- Extended oil life: excellent thermal and oxidation stability

## PERFORMANCE PROFILE

### SPECIFICATIONS

ACURA - 08200-9016A  
ACURA - ATF TYPE 3.0  
ATF - L 12108  
BMW - 83 22 2 289 720  
BMW - 83 22 2 305 397  
BMW - 83222152426

BMW - 83225A12A00  
BMW - ATF3+  
CHRYSLER - 68157995AA  
FIAT - 9.55550-AV5  
HONDA - 08200-9017  
HONDA - ATF TYPE 3.1

JAGUAR - 02JDE26444  
LAND ROVER - LR023288  
LAND ROVER - LR023289  
MB - 236.82  
MOPAR - 68157995AB  
MOPAR - 68218925AA

NISSAN - MATIC-R  
VW - G 055 162  
VW - G 060 162  
ZF - S671 090 312  
ZF - TE-ML 11

## TYPICAL CHARACTERISTICS

TEST	METHOD	UNIT	AVERAGE RESULTS
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	31.9
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	6.32
Viscosity index	ASTM D2270		153
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	210
Colour	VISUAL		GREEN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.