

CHAMPION MOTO HP 2T TRANSMISSION OIL 10W30

This mineral lubricant is developed for gearboxes in motorcycles with a two-stroke engine equipped with an integrated clutch. Its special composition assures easy gear shifting and controls the slipping characteristics of the clutch, resulting in a smoother riding experience.

APPLICATIONS

This oil is qualified for all gearboxes with a clutch in an oil bath. It combines excellent deterging properties with a very resistant oil film and good extreme pressure properties.

FEATURES

Less vibration: smoother ride

Optimised friction characteristics: improved transmission protection

Broad material compatibility: fewer fluids required to maintain several motorcycles

SPECIFICATIONS

API GL-3

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.865
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	68.1
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.0
Viscosity index	ASTM D2270		153
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	210
Colour	VISUAL		GREEN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

