

WOLF WAY LUBRICANT

ISO 68

14/04/2025
4531

This oil is particularly used for the lubrication of machine tool slideways. By the use of special additives, the adhesive and lubricity properties are increased and shocks (so-called stick-slip) are avoided.

APPLICATIONS

This oil is specifically suitable for slideways of machine tools, chains, reductions, and general lubrication of machines when oil spattering has to be avoided.

FEATURES

Stick-slip performance: good stick-slip test results
Extreme pressure properties: mild EP properties

SPECIFICATIONS

AFNOR	NF E 48-603 HM	DIN	51524 Part 2
DIN	51502 CGLP	CINCCINATI	MILACRON P-47

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.884
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	69.2
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	9
Viscosity index	ASTM D2270		104
A.N. (Colorimetric)	ASTM D974	mg KOH/g	0.40
Pour point	ASTM D6892	°C	-27
Flash Point COC	ASTM D92	°C	210

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.