

# WOLF ESSENTIAL ISO 68

29/10/2025  
75837

This mineral fluid stabilises the hydraulic performance with its formulation with anti-wear and anti-corrosion additives. This product may not be available in your region. Please, consult your local sales contact for more information.

## APPLICATIONS

Can be used in a range of different demanding hydraulic systems. It is adapted to meet the DIN 51524 Part 1 specification.

## FEATURES

Anti-wear and oxidation stability: superior protection.  
Anti-foam properties: excellent anti-foam properties.

## SPECIFICATIONS

DIN	51524 Part 2	ISO	6743-4, HM
ISO	11158, HM		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.879
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	68.0
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	8.6
Viscosity index	ASTM D2270		102
Pour point	ASTM D6892	°C	-30
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

