

WOLF RACING TRANS/AXLE LS 75W-140 ESTER

14/04/2025
65524

This is a sustainable RRBO high performance gearbox and transaxle lubricant, enriched with ester and PAO, for racing vehicles offering an excellent anti-wear and EP protection, a better resistance at high temperatures and a longer oil life time.

APPLICATIONS

This sustainable RRBO lubricant can be used in gearboxes, transaxles and differentials with or without limited slip of racing vehicles.

FEATURES

Anti-wear protection: extended component life.
Extended oil life: excellent thermal and oxidation stability.

SPECIFICATIONS

API	GL-5	HEWLAND	SFU
API	GL-6	HOLLINGER	SFU
API	MT-1	MACK	GO-J
MIL	L-2105 B	MB	235.61
MIL	L-2105 C	M-SPORT	Rally3/Rally4/Rally5/R1/R2/R3
MIL	L-2105 D	NISSAN	2189E
MIL	L-2105 E	RICARDO	SFU
SAE	J 2360	SADEV	SFU
ARVIN MERITOR	0-76-N	SALISBURY	SFU
BMW	83 22 1 470 080	SCANIA	STO 1:0
BMW	83 22 2 282 583	SCANIA	STO 2:0A
BMW	83 22 9 407 803	VW	G 052 539
BMW	83 22 9 407 870	X-TRAC	SFU
BMW	MSP/A	ZF	TE-ML 05A
CHRYSLER	68218658AA	ZF	TE-ML 05B
CHRYSLER	MS 8985	ZF	TE-ML 05C
DANA	SFU	ZF	TE-ML 05D
DREXLER	SFU	ZF	TE-ML 07A
FERRARI	PAKELO GLOBAL MULTIGEAR DLS	ZF	TE-ML 12D
FORD	ESW-M2C104-A	ZF	TE-ML 12N
FORD	ESW-M2C119-A	ZF	TE-ML 16F
FORD	WSS-M2C187-A	ZF	TE-ML 16G
FORD	WSS-M2C192A+/M2C118-A	ZF	TE-ML 19C
GM	12346140	ZF	TE-ML 21A
GM	1942386	ZF	TE-ML 21C
GM	9986226	ZF	TE-ML 21D
GM	9986290		

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.898
Kinematic viscosity at 40°C	ASTM D445	mm²/s	179
Kinematic viscosity at 100°C	ASTM D445	mm²/s	24.3
Viscosity index	ASTM D2270		167
Pour point	ASTM D6892	°C	-51
Colour	VISUAL		LIGHT BROWN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

