

# WOLF AROW HV ISO 46

02/03/2026  
4406

A high viscosity index paraffinic oil, based on selected ingredients, specifically intended for use in hydraulic circuits. Superior performance in keeping the system clean by reducing the formation of deposits. It also demonstrates good filterability, water separation, and quick air release.

## APPLICATIONS

Hydraulic systems, functioning at very variable temperatures and at high pressures. Gear boxes, which require an oil with an increased viscosity index and assuring a mechanical and chemical stability. Regulation systems and hydraulic steering.

## FEATURES

Anti-wear and oxidation stability: superior protection  
Anti-foam properties: excellent anti-foam properties  
Temperature stability: superior viscosity stability

## SPECIFICATIONS

AFNOR	NF E 48-603 HV	JCMAS	HK P041
AFNOR	NF E 48-690	PARKER (DENISON)	HF-0, HF-1, HF-2
AFNOR	NF E 48-691	SAE	MS1004
AGMA	9005-E02-RO	SEB	181222
AIST	126 (US Steel)	CINCINNATI	MACHINE P-70 (ISO 46)
AIST	127 (US Steel)	DENISON	HF-0, HF-1, HF-2
ASTM	D6158 HV	EATON VICKERS	I-286-S
DIN	51524 Part 3	EATON VICKERS	M-2950-S
ISO	11158, HV	EATON	E-FDGN-TB002-E
ISO	20763	EATON	M-2950-S (35VQ25 pump test)
ISO	6743-4, HV	GM	LS2 AW hyd.oil

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.876
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	46.0
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	8.1
Viscosity index	ASTM D2270		150
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	218

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolflubes.com](http://www.wolflubes.com)

