

CHAMPION MOTO HP 4T 5W40

Thanks to its stable mineral and synthetic base oils and the advanced additive package, this four-stroke motorcycle engine oil guarantees a smooth and stable ride. The balanced formula is developed to exactly suit the needs of motorcycle enthusiasts looking for optimal riding comfort. Its good fluidity at low temperatures guarantees complete engine protection right after starting the engine.

APPLICATIONS

This lubricant is developed for the engines, transmissions and wet clutches of four-stroke motorcycles. It is perfectly balanced to meet the requirements of several manufacturers.

FEATURES

Extended motorcycle lifespan thanks to the oil's protective properties.: Extended motorcycle lifespan thanks to the oil's protective properties.

Protects the original riding comfort.: Protects the original riding comfort.

Simpler fluid management thanks to the oil's broad applicability.: Simpler fluid management thanks to the oil's broad applicability.

SPECIFICATIONS

API

SL

JASO

MA2

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.846
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	79.6
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.8
Viscosity index	ASTM D2270		179
B.N. [HCL04 method]	ASTM D2896	mg KOH/g	6.1
Pour point	ASTM D6892	°C	-39
Colour	VISUAL		BROWN
CCS viscosity at -30°C	ASTM D5293	mPa.s	4300

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

