

CHAMPION NEW ENERGY MULTI VEHICLE ATF

This is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions, meeting the requirements of most American, Japanese and European manufacturers.

APPLICATIONS

Its versatile nature guarantees it can be used in automatic transmissions and torque convertors for most passenger cars, off-road vehicles and SUVs.

FEATURES

Frictional properties: very smooth gear shifting, no vibration
Anti-wear protection: significantly extended transmission life
Extended oil life: excellent thermal and oxidation stability

SPECIFICATIONS

IDEMITSU	K17	CHRYSLER	AS68RC ATF
JASO	M315, Class 1A	CHRYSLER	ATF +3 AND +4
AISIN-WARNER	AW-1	CHRYSLER	MD 7176E
AISIN-WARNER	JWS 3309	CHRYSLER	MS 9602
AISIN-WARNER	JWS 3314	DTFR	13C100
AISIN-WARNER	JWS 3317	DTFR	13C110
ALFA ROMEO	HP20	DTFR	13C120
ALLISON	C4	DTFR	13C140
ALLISON	TES 295	DTFR	13C150
ALLISON	TES 389	DTFR	13C170
BENTLEY	PY112995PA	DTFR	13C180
BMW	81 22 9 400 275	DTFR	388100
BMW	81 22 9 401 220	FIAT	9.55550-AV1
BMW	83 22 0 024 359	FIAT	9.55550-AV4
BMW	83 22 0 026 922	FORD	ESP-M2C138-CJ
BMW	83 22 0 142 516	FORD	ESP-M2C166-H
BMW	83 22 0 403 248	FORD	M2C-202B
BMW	83 22 0 403 249	FORD	MERCON
BMW	83 22 2 152 426	FORD	MERCON V
BMW	83 22 2 344 206	FORD	WSS-M2C195-A
BMW	83 22 2 355 599	FORD	WSS-M2C919-E
BMW	83 22 9 407 765	FORD	WSS-M2C922-A1
BMW	83 22 9 407 807	FORD	WSS-M2C924-A
BMW	ATF 3	GM	1940700
BMW	ATF 4	GM	1940767
BMW	ATF 6	GM	210005966
BMW	ETL 7045E	GM	22717466
BMW	ETL 8072B	GM	88900925
BMW	LA 2634	GM	9986195
BMW	LT 71141	GM	DEXRON II
BMW	ZF 5HP18FL,5HP24,5HP30	GM	DEXRON II-D
CHRYSLER	05127382AA	GM	DEXRON II-E

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com



GM	DEXRON III	MITSUBISHI	Diaqueen J3
GM	DEXRON III-G	MITSUBISHI	Diaqueen SK
GM	DEXRON III-H	MITSUBISHI	Diaqueen SP-II
GM	DEXRON TYPE A, SUFFIX A	MITSUBISHI	Diaqueen SP-III
HONDA	ATF Z-1	MITSUBISHI	Diaqueen SP-IV
HONDA	Premium	MITSUBISHI	SFU
HYUNDAI	SFU	MITSUBISHI	V5AWF
HYUNDAI	SP-II	MOPAR	ATF +3
HYUNDAI	SP-III	MOPAR	ATF +4
ISUZU	BESCO ATF-II	NISSAN	999MP-ATFD3MP
ISUZU	BESCO ATF-III	NISSAN	D3m
ISUZU	Genuine	NISSAN	MATIC-D
ISUZU	PSF	NISSAN	MATIC-J
ISUZU	SCS Fluid	NISSAN	MATIC-K
JAGUAR	ATF 3403 M115	NISSAN	MATIC-W
JAGUAR	Fluid 8432	OPEL	GM 1940700
JAGUAR	JLM 20238	OPEL	GM 1940767
JAGUAR	JLM 20292 [LA 3403-M115]	OPEL	GM 21005966 Transaxle
JAGUAR	JLM 21044	OPEL	GM 2217466
JEEP	ATF 3	OPEL	GM 9986185
KIA	ATF Red -1K	PORSCHE	000.043.202.28
KIA	SP-II	PORSCHE	000.043.204.63
KIA	SP-III	PORSCHE	000.043.205.09
LAND ROVER	LR002748	PORSCHE	000.043.207.00
LAND ROVER	N402	PORSCHE	999.917.547.00[A2]
MAN	339 V1/Z1	PORSCHE	JWS 3309 [Cayenne]
MAN	339 V2/Z2	PORSCHE	LA 3403-M115
MAN	339 Z3	PORSCHE	T-IV [JWS 3309]
MASERATI	231603	PSA	P/N Z 000169756
MAZDA	ATF 3317	PSA	ZF 4HP20
MAZDA	ATF D-II	RENAULT	A14
MAZDA	ATF F-1	RENAULT	DPO/AL4
MAZDA	ATF FZ	RENAULT	MATIC-D2
MAZDA	ATF M-III	RENAULT	Samsung SATF-D
MAZDA	ATF M-V [Type M5]	SAAB	T-IV [JWS 3309]
MAZDA	ATF N-1	SAAB	Transmax J- TIV
MAZDA	ATF S-1	SCION	T-II
MB	236.1	SCION	T-III
MB	236.10	SCION	T-IV
MB	236.11	SUBARU	ATF 5AT
MB	236.12	SUBARU	ATF, ATF HP
MB	236.14	SUBARU	K0140Y0700
MB	236.2	SUZUKI	AT OIL 5006
MB	236.3	SUZUKI	ATF 2324K
MB	236.5	SUZUKI	ATF 2326
MB	236.6	SUZUKI	ATF 3310
MB	236.7	SUZUKI	ATF 3311
MB	236.8	SUZUKI	ATF JWS 3309
MB	236.9	SUZUKI	Dexron III
MB	236.91	TOYOTA	TYPE T-II
MINI	83 0 402 42	TOYOTA	TYPE T-III
MINI	T-IV	TOYOTA	TYPE T-IV
MITSUBISHI	4030401	VOITH	55.6335[G607. G1363]
MITSUBISHI	ATF J2	VOITH	DIWA #013S
MITSUBISHI	Diaqueen ATF MA1	VOLVO Constr. Equip. [VCE]	1273,41
MITSUBISHI	Diaqueen ATF-PA	VOLVO	1161540

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com



VOLVO	97325	VW	TL 5612
VOLVO	JWS 3309	ZF	TE-ML 02F
VW	G 052 025	ZF	TE-ML 03D
VW	G 052 055	ZF	TE-ML 04D
VW	G 052 162	ZF	TE-ML 09
VW	G 052 533	ZF	TE-ML 11A
VW	G 052 990	ZF	TE-ML 11B
VW	G 055 025	ZF	TE-ML 14A
VW	G 055 540	ZF	TE-ML 14B
VW	G 060 162	ZF	TE-ML 14C
VW	G US 000 162	ZF	TE-ML 16L
VW	TL 52 162	ZF	TE-ML 17C

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	36.3
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	6.84
Viscosity index	ASTM D2270		150
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	218
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

