

# WOLF OFFICIALTECH 10W-30 IL HC

24/11/2025  
16187

This semi-synthetic oil offers low wear, low emissions, and a strong fuel economy. Its carefully synthesized additive package targets soot and deposits to keep the engine clean.

## APPLICATIONS

This engine oil has been specifically developed to meet the challenging requirements of the latest ILSAC GF-7 A standard where fuel economy and CO2 reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

## FEATURES

Cold start: excellent fluidity at low temperature

Fuel economy: excellent fuel economy and low exhaust emissions

Total engine protection: performance in keeping the engine clean

## SPECIFICATIONS

API	SN Plus	ILSAC	GF-5
API	SN/RC	ILSAC	GF-6 A
API	SP	ILSAC	GF-7 A
API	SP/RC	CHRYSLER	MS 6395
API	SQ	GM	6094M
API	SQ/RC		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.849
Kinematic viscosity at 40°C	ASTM D445	mm²/s	64.2
Kinematic viscosity at 100°C	ASTM D445	mm²/s	10.6
Viscosity index	ASTM D2270		155
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	7.4
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolflubes.com](http://www.wolflubes.com)

