WOLF MULTI MOLY EP 0 ARCTIC

25/09/2026
9185

This Multi Moly Arctic Grease EP 0 is a calcium complex and lithium complex thickened lubricating grease based on mineral oil. It contains antioxidants, corrosion inhibitors and molybdebum disulphide.This grease does not contain conventional EP and AW additives since they are built in as an integral part of the soap structure.

APPLICATIONS

This modern high-performance grease is suitable for extreme heavy industry applications operating in cold conditions. The extreme load carrying capacity and the excellent water resistance make this grease a perfect choice for heavily loaded open gears and similar applications.The molybdenum disulphide provides extra protection in applications with slow moving or oscillating bearings, but should be avoided for rolling bearings at high speed.

FEATURES

Load capacity: high resistance to shock loads
Temperature stability: great low temperature mobility
Water resistance: very good water resistance

SPECIFICATIONS

DIN	51502	ISO	12924
DIN	OGFP0G-50	ISO	L-XE(F)BIB0

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 20°C	ASTM D4052	g/ml	0.970
Colour	VISUAL		BLACK
NLGI Classification	ASTM D217		0
Flow pressure at -50°C	DIN 51805	mbar	< 1400
Base Oil Viscosity at 40 °C	ASTM D7152	cSt	45
Four Ball Weld Load	ASTM D2596/ DIN51350:4	N	6500

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV