

WOLF VITALTECH ATF D III

03/04/2026
3006

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This is an oil with a very high viscosity index for most automatic transmissions. The improved fluidity at low temperatures ensures optimum performance in all conditions. Its exceptional frictional characteristics provide smooth switching and driving comfort.

APPLICATIONS

This oil is used in automatic transmissions, torque converters, power steering and hydraulic circuits, for which the manufacturers prescribe a product, which meets the General Motors ATF TYPE Dexron III or Dexron II E and Ford Mercon-requirements.

FEATURES

Frictional properties: smooth shift performance
Anti-wear protection: extended transmission life
Extended oil life: excellent thermal and oxidation stability

SPECIFICATIONS

| | |
|---------|---------------------|
| ALLISON | C4 |
| DTFR | 13C140 |
| DTFR | 13C150 |
| DTFR | 13C170 |
| FORD | MERCON |
| GM | 6417-M DEXRON III-G |
| GM | DEXRON II-D |
| GM | DEXRON III-H |
| MAN | 339 V1/Z1 |
| MB | 236.5 |
| MB | 236.6 |
| MB | 236.93 |
| PSA | 9730 AC |
| VOITH | H55.6335xx |
| VOLVO | STD 1273,25 (97325) |
| VOLVO | STD 1273,35 (97335) |
| VOLVO | STD 1273,37 (97337) |
| VOLVO | STD 1273,40 (97340) |
| VOLVO | STD 1273,41 (97341) |
| ZF | TE-ML 03D |
| ZF | TE-ML 04D |
| ZF | TE-ML 05L |
| ZF | TE-ML 09 |
| ZF | TE-ML 11B |
| ZF | TE-ML 14A |
| ZF | TE-ML 17C |
| ZF | TE-ML 21L |

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|-------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.847 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 33.9 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 7.1 |
| Viscosity index | ASTM D2270 | | 179 |
| Pour point | ASTM D6892 | °C | -45 |
| Brookfield viscosity at -40°C | ASTM D2983 | mPa.s | 17500 |
| Flash Point COC | ASTM D92 | °C | 196 |
| Colour | VISUAL | | RED |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

