

WOLF OFFICIALTECH ATF LIFE PROTECT 8

14/04/2025
3016

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6, 8 and 9-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting.

APPLICATIONS

Exclusively intended for the ZF 6, 8 and 9 speed automatic transmissions, as fitted in VW, BMW, Jaguar, Land Rover, Jeep, Chrysler and FIAT group.

FEATURES

Anti-wear protection: significantly extended transmission life

Frictional properties: very smooth gear shifting, no vibration

Extended oil life: excellent thermal and oxidation stability

SPECIFICATIONS

ACURA	08200-9016A	HONDA	ATF TYPE 3.1
ACURA	ATF TYPE 3.0	JAGUAR	02JDE26444
ATF	L 12108	LAND ROVER	LR023288
BMW	83 22 2 289 720	LAND ROVER	LR023289
BMW	83 22 2 305 397	MB	236.82
BMW	83222152426	MOPAR	68157995AB
BMW	83225A12A00	MOPAR	68218925AA
BMW	ATF3+	VW	G 055 162
CHRYSLER	68157995AA	VW	G 060 162
FIAT	9.55550-AV5	ZF	S671 090 312
HONDA	08200-9017	ZF	TE-ML 11

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	31.9
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	6.32
Viscosity index	ASTM D2270		153
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	<=20000
Flash Point COC	ASTM D92	°C	210
Colour	VISUAL		GREEN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

