

WOLF OE LEVELTECH 5W30 LL III

14/04/2025
75602

This full synthetic engine oil is formulated to meet the specifications of different OEMs. It reaches ACEA and API requirements by balancing excellent fluidity with advanced engine protecting, regardless the driving conditions. This product may not be available in your region. Please, consult your local sales contact for more information.

APPLICATIONS

Its formulation is designed to meet the VW 504.00 and 507.00 specifications. This engine oil can be used to service a range of different EURO 4 and EURO 5-engines equipped with diesel particulate filters.

FEATURES

Aftertreatment protection: full aftertreatment device protection.

Total engine protection: outstanding engine cleanliness and durability.

SPECIFICATIONS

ACEA	C2	MB	229.52
ACEA	C3	OPEL	GM-LL-A-025
API	approval SN	OPEL	GM-LL-B-025
API	CF	OPEL	OV 040 1547 - D30
BMW	LOGLIFE-04	PORSCHE	C30
FIAT	9.55535-S3	VW	503 01
MB	229.31	VW	504 00/507 00
MB	229.51		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.856
Kinematic viscosity at 40°C	ASTM D445	mm²/s	68.0
Kinematic viscosity at 100°C	ASTM D445	mm²/s	11.7
Viscosity index	ASTM D2270		169
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	8.3
Pour point	ASTM D6892	°C	-39
Sulfated Ash	ASTM D874	Mass %	0.7
Flash Point COC	ASTM D92	°C	230

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

