

# CHAMPION PROPULSE TT BRAKE FLUID 260

This DOT 3/4 brake fluid guarantees you a stable and reliable performance thanks to its high chemical stability, oxidation stability and excellent resistance against residue formation. These properties turn this fluid into an excellent choice for servicing motorcycles from different manufacturers.

## APPLICATIONS

It is suitable for all hydraulic brake circuits where the manufacturer recommends a fluid, which meets the specifications mentioned below. It is also suitable for numerous steering and clutch systems and can be used from -40°C to 260°C.

## FEATURES

Boiling point: high boiling point, safe braking

Anti-corrosion properties: complete brake system protection

Broad compatibility: service several motorcycles with one fluid

## SPECIFICATIONS

<b>FMVSS</b>	116 DOT 4	<b>SAE</b>	J 1703
<b>FMVSS</b>	116 DOT3	<b>SAE</b>	J 1704
<b>ISO</b>	4925 Class 3&4		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Water content	DIN 51777 T1	ppm	< 2000
pH	ASTM D1287		8.65
Equilibrium Reflux Boiling Point [ERBP]	ASTM D1120	°C	269
Wet Equilibrium Reflux Boiling Point [WERBP]	ASTM D1120	°C	159
Density at 20°C	ASTM D4052	g/ml	1.039
Colour	VISUAL		Colourless to Amber

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

