

WOLF RACING TRANS 75W-140 ESTER

14/04/2025
65520

This is a full synthetic Extreme Pressure high performance gearbox and transaxle lubricant, enriched with ester, for racing vehicles offering an excellent anti-wear protection, a better resistance at high temperatures and a longer oil life time. It is blue colored.

APPLICATIONS

This lubricant can be used in gearboxes, transaxles and differentials with or without limited slip of racing vehicles.

FEATURES

Anti-wear protection: extended component life.
Extended oil life: excellent thermal and oxidation stability.

SPECIFICATIONS

API	GL-5	MB	235.61
API	GL-6	M-SPORT	Rally3/Rally4/Rally5/R1/R2/R3
API	MT-1	NISSAN	2189E
MIL	L-2105 B	RICARDO	SFU
MIL	L-2105 C	SADEV	SFU
MIL	L-2105 D	SALISBURY	SFU
MIL	L-2105 E	SCANIA	STO 1:0
SAE	J 2360	SCANIA	STO 2:0A
ARVIN MERITOR	0-76-M	VW	G 052 539
BMW	83 22 1 470 080	ZF	TE-ML 05A
BMW	83 22 2 282 583	ZF	TE-ML 05B
BMW	83 22 9 407 803	ZF	TE-ML 05C
BMW	83 22 9 407 870	ZF	TE-ML 05D
BMW	MSP/A	ZF	TE-ML 07A
CHRYSLER	68218658AA	ZF	TE-ML 12D
CHRYSLER	MS 8985	ZF	TE-ML 12N
DANA	SFU	ZF	TE-ML 16F
DREXLER	SFU	ZF	TE-ML 16G
FERRARI	PAKELO GLOBAL MULTIGEAR DLS	ZF	TE-ML 18
FORD	ESW-M2C104-A	ZF	TE-ML 19C
FORD	ESW-M2C119-A	ZF	TE-ML 21A
FORD	WSS-M2C187-A	ZF	TE-ML 21C
FORD	WSS-M2C192A+/M2C118-A	ZF	TE-ML 21D
GM	12346140		
GM	1942386		
GM	9986226		
GM	9986290		
HEWLAND	SFU		
HOLLINGER	SFU		
MACK	GO-J		

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.898
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	174
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	24.5
Viscosity index	ASTM D2270		173
Pour point	ASTM D6892	°C	-51
Colour	VISUAL		BLUE

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

