

CHAMPION OEM SPECIFIC

5W-30 MS-GD

This synthetic engine oil guarantees a cleaner and better performing engine without lowering the oil drain interval.

It is based on carefully selected very high quality base oils and formulated using the latest technology for catalyst compatible engine oils.

The broad applicability of this engine oil enables you to offer perfect maintenance to different vehicles of several major brands.

APPLICATIONS

This engine oil can be used in systems with or without exhaust gas aftertreatment where C2 [PSA] or C3 [German OEM's] engine oils are required.

Furthermore, this engine oil has an official GM dexosD approval. DexosD meets or exceeds the performance of dexos2 and is backward compatible.

FEATURES

Aftertreatment protection: full aftertreatment device protection.

Fuel economy: lower fuel consumption and CO2 emissions.

Total engine protection: outstanding engine cleanliness and durability.

SPECIFICATIONS

ACEA	C2	VW	505 00
ACEA	C3	VW	505 01
API	CF		
API	SN		
API	SP		
BMW	LOGLIFE-04		
CHRYSLER	MS 11106		
FIAT	9.55535-S3		
FORD	WSS-M2C917-A		
GM	approval dexos™2		
GM	approval dexos™D		
GM	dexos™1 Gen 3		
HYUNDAI	SFU		
KIA	SFU		
MB	226.5		
MB	229.31		
MB	229.51		
MB	229.52		
OPEL	GM-LL-A-025		
OPEL	GM-LL-B-025		
OPEL	OV 040 1547 - D30		
OPEL	OV 040 1547 - G30		
RENAULT	RN 0700		
RENAULT	RN 0710		
VW	502 00 < 2017		

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com





TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	75.56
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	12.4
Viscosity index	ASTM D2270		163
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	8.0
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	230

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

