

WOLF OE LEVELTECH OW-30 CORE

08/07/2026
75655

This synthetic based engine oil is designed to meet the core requirements of ACEA, API and ILSAC for passenger cars. It offers complete protection of both the aftertreatment system and the engine, regardless the driving conditions.

APPLICATIONS

Formulated to meet recent OEM specifications. It can be used to service a wide range of EURO 4 and EURO 5-engines of different manufacturers, with or without diesel particulate filter.

FEATURES

Broad coverage: reduced lubricant costs.

Significant friction reduction: improved fuel efficiency and lowered emissions.

SPECIFICATIONS

ACEA	C2
ACEA	C3
API	SN Plus
API	SP
API	SQ
CHINESE STANDARD	GB VI A
CHINESE STANDARD	GB VI B
ILSAC	GF-6 A
FIAT	9.55535-DS1
FIAT	9.55535-GS1
FIAT	9.55535-S3
GENESIS	SFU
HONDA	SFU
HYUNDAI	SFU
KIA	SFU
LANCIA	SFU
LEXUS	SFU
MASERATI	SFU
MB	227.61
MB	229.31
MB	229.51
MB	229.52
MB	229.61
MINI	SFU
MITSUBISHI	SFU
ROLLS-ROYCE	SFU
SSANG YONG	SFU
SUZUKI	SFU
TOYOTA	SFU

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.843
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	69.5
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	12.2
Viscosity index	ASTM D2270		175
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	8.5
Pour point	ASTM D6892	°C	-42
Sulfated Ash	ASTM D874	Mass %	0.78
Flash Point COC	ASTM D92	°C	225

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

