

MULTI VEHICLE ATF

14/04/2025
3010

This is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions , meeting the requirements of most American, Japanese and European manufacturers.

APPLICATIONS

Its versatile nature guarantees it can be used in automatic transmissions and torque convertors for most passenger cars, off-road vehicles and SUVs.

FEATURES

Frictional properties: very smooth gear shifting, no vibration
Anti-wear protection: significantly extended transmission life
Extended oil life: excellent thermal and oxidation stability

SPECIFICATIONS

JASO	M315, Class 1A	DTFR	13C170
AISIN-WARNER	JWS 3309	DTFR	13C180
AISIN-WARNER	JWS 3314	FIAT	9.55550-AV1
AISIN-WARNER	JWS 3317	FIAT	9.55550-AV4
ALFA ROMEO	HP20	FORD	MERCON
ALLISON	C4	FORD	MERCON V
ALLISON	TES 295	FORD	WSS-M2C195-A
ALLISON	TES 389	FORD	WSS-M2C919-E
BMW	81 22 9 400 275	FORD	WSS-M2C922-A1
BMW	81 22 9 401 220	GM	DEXRON II-D
BMW	83 22 0 026 922	GM	DEXRON II-E
BMW	83 22 0 403 248	GM	DEXRON III-G
BMW	83 22 0 403 249	GM	DEXRON III-H
BMW	83 22 2 344 206	HONDA	ATF Z-1
BMW	83 22 2 355 599	HYUNDAI	ATF RED 1K
BMW	83 22 9 407 765	HYUNDAI	SP-II
BMW	ATF 4	HYUNDAI	SP-III
BMW	ATF 6	JAGUAR	JLM 20292 (LA 3403-M115)
BMW	ETL 7045E	JAGUAR	JLM 21044
BMW	ETL 8072B	LAND ROVER	LR002748
BMW	LA 2634	LAND ROVER	N402
BMW	LT 71141	MAZDA	ATF F-1
CHRYSLER	AS68RC ATF	MAZDA	ATF M-V (Type M5)
CHRYSLER	ATF +3 AND +4	MB	236.10
CHRYSLER	MS 9602	MB	236.11
DTFR	13C100	MB	236.3
DTFR	13C110	MB	236.5
DTFR	13C140	MB	236.6
DTFR	13C150	MB	236.7

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfoil.com

WOLFOIL
CORPORATION

<i>MB</i>	236.8	<i>TOYOTA</i>	TYPE T
<i>MB</i>	236.9	<i>TOYOTA</i>	TYPE T-III
<i>MB</i>	236.91	<i>TOYOTA</i>	TYPE T-IV
<i>MITSUBISHI</i>	4030401	<i>VOLVO Constr. Equip. (VCE)</i>	1273,41
<i>MITSUBISHI</i>	ATF J2	<i>VOLVO</i>	1161540
<i>MITSUBISHI</i>	DIA QUEEN ATF-PA	<i>VW</i>	G 052 025
<i>MITSUBISHI</i>	V5AWF	<i>VW</i>	G 052 055
<i>NISSAN</i>	MATIC-D	<i>VW</i>	G 052 162
<i>NISSAN</i>	MATIC-J	<i>VW</i>	G 052 533
<i>NISSAN</i>	MATIC-K	<i>VW</i>	G 052 990
<i>NISSAN</i>	MATIC-W	<i>VW</i>	G 055 025
<i>PORSCHE</i>	LA 3403-M115	<i>VW</i>	G US 000 162
<i>PSA</i>	P/N Z 000169756	<i>ZF</i>	TE-ML 11A
<i>RENAULT</i>	MATIC-D2	<i>ZF</i>	TE-ML 11B

TYPICAL CHARACTERISTICS

<i>Test</i>	<i>Method</i>	<i>Unit</i>	<i>Average results</i>
<i>Density at 15°C</i>	<i>ASTM D4052</i>	<i>g/ml</i>	<i>0.851</i>
<i>Kinematic viscosity at 40°C</i>	<i>ASTM D445</i>	<i>mm²/s</i>	<i>36.3</i>
<i>Kinematic viscosity at 100°C</i>	<i>ASTM D445</i>	<i>mm²/s</i>	<i>6.84</i>
<i>Viscosity index</i>	<i>ASTM D2270</i>		<i>150</i>
<i>Pour point</i>	<i>ASTM D6892</i>	<i>°C</i>	<i>-48</i>
<i>Brookfield viscosity at -40°C</i>	<i>ASTM D2983</i>	<i>mPa.s</i>	<i><=20000</i>
<i>Flash Point COC</i>	<i>ASTM D92</i>	<i>°C</i>	<i>218</i>
<i>Colour</i>	<i>VISUAL</i>		<i>RED</i>

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfoil.com

WOLFOIL
CORPORATION