

CHAMPION CENTRAL HYDRAULIC FLUID

This is a full synthetic lubricant based on carefully selected very high quality base oils. It is a hydraulic "multipurpose" fluid specifically designed for the use in all circuits and in a temperature range between -40°C and 130°C. This fluid has a very high viscosity index, an exceptional oxidation stability, anti-foam and anti-rust properties. It has a unique friction reducing additive for reduction of wear and noise production of the hydraulic pump.

APPLICATIONS

This multipurpose fluid is to be used in the following applications : hydraulic suspensions, shock absorbers, hydrostatic controls, centralized hydraulic circuits, power steering and level controls. It is also suitable for suspension and steering wheel systems of MAN trucks.

FEATURES

Pour point: excellent low temperature properties

SPECIFICATIONS

CHF	11S	HYUNDAI	00232-19017
CHF	202	HYUNDAI	03100-00130
DIN	51524 T3	HYUNDAI	PSF-4
ISO	7308	KIA	PSF-IV
ALFA ROMEO	15081616 CS SPEED	LAND ROVER	Cold Climate PAS Fluid 14315
AUDI	G 002 000		LRN2261
AUDI	G 002 500	LAND ROVER	LR 003 401
AUDI	G 004 000	MAN	M3289
BENTLEY	JNV862564F	MB	001989240310
BENTLEY	RH 5000	MB	001989240312
BMW	81 22 9 407 758	MB	343.0
BMW	82110148132	MB	344.0
BMW	82111468041	MB	345.0
BMW	83 19 2 179 990	MB	345.1
BMW	83290429576	MB	Q1320001
CHRYSLER	MS 10838	MINI	83 29 0 429 576
CHRYSLER	MS 11655	MITSUBISHI	Diaqueen PSF
CHRYSLER	MS 5931	NISSAN	E-PSF
DTFR	31B120	OPEL	B 040 0070
FENDT	X902011622	OPEL	B 040 2012
FIAT	14621616	OPEL	GM 1940715
FIAT	9.55550-AG3	OPEL	GM 1940766
FIAT	9.55550-SA1	PORSCHE	000.043.203.33
FIAT	F005.F98	PORSCHE	000.043.204.89
FORD	1 384 110	PORSCHE	000.043.206.56
FORD	WSS-M2C204-A	PORSCHE	000.043.206.74
GM	9985835	PORSCHE	999.917.551.00
		PSA	9979 A4

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com



PSA	S71 2710	SUZUKI	99000M24121-135
SAAB	3032380	SUZUKI	AMT Actuator Fluid
SAAB	9-3 power steering	VOLVO	1161529-1
SAAB	9316 0548	VOLVO	30741424
SAAB	93160548	VOLVO	8713081
SAAB	9-5 power steering	VW	G 002 000
SEAT	G 002 000	VW	G 002 500
SEAT	G 002 500	VW	G 004 000
SEAT	G 004 000	VW	G 004 012
SKODA	G 002 000	VW	TL 521 46
SKODA	G 002 500	ZF	TE-ML 02K
SKODA	G 004 000	ZF	TE-ML 09B

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Color	ASTM D1500		green
Density at 15°C	ASTM D4052	g/ml	0.865
Kinematic viscosity at 40°C	ASTM D445	mm²/s	19.2
Kinematic viscosity at 100°C	ASTM D445	mm²/s	6.3
Viscosity index	ASTM D2270		322
Pour point	ASTM D6892	°C	-54
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	840
Flash Point COC	ASTM D92	°C	156

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

