WOLF ESSENTIAL
SN/CF 5W30

25/09/2026
75616

This semi-synthetic engine oil is designed to meet the core requirements of API for passenger cars. It offers high temperature piston deposit and sludge control.

APPLICATIONS

This engine oil can be used for the maintenance of engines from different manufacturers, with or without aftertreatment system.

FEATURES

Engine protection: ensures high level of the engine cleanliness

SPECIFICATIONS

ACEA	A3/B4	OPEL	GM-LL-B-025
API	SN/CF	VW	502 00
MB	229.1	VW	505 00
OPEL	GM-LL-A-025		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.855
Kinematic viscosity at 40°C	ASTM D445	mm²/s	69.5
Kinematic viscosity at 100°C	ASTM D445	mm²/s	11.8
Viscosity index	ASTM D2270		166
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	10.1
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	216

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV