

WOLF FLUSHING OIL

14/04/2025
4524

This is a low viscosity mineral oil with good flushing and cleaning properties.

APPLICATIONS

It is primarily used for flushing the oil sump and lubrication systems of internal combustion engines. It can also be used for flushing transmissions and gear boxes, to remove dirt and wear particles.

FEATURES

Cleaning properties: very good detergent and dispersant characteristics

SPECIFICATIONS

ISO 6743/10

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.900 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 20.8 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 3.8 |
| Viscosity index | ASTM D2270 | | 45 |
| Pour point | ASTM D6892 | °C | -33 |
| Anilin point | ASTM D611 | °C | 78 |
| Flash Point COC | ASTM D92 | °C | 170 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfubcs.com

