

CHAMPION MOTO HP 2T SCOOTER

This semi-synthetic two-stroke scooter engine oil with an advanced additive package guarantees a smooth and stable ride. The balanced formula is developed to exactly suit the needs of scooter enthusiasts looking for optimal riding comfort.

APPLICATIONS

This lubricant is developed for the engines of 2-stroke scooters. Please follow the dosage recommendations of the equipment manufacturer.

FEATURES

Engine protection: extended scooter lifespan thanks to the oil's protective properties

Riding comfort: protects the original riding comfort

Economic properties: simpler fluid management thanks to the oil's broad applicability

SPECIFICATIONS

API	TC	JASO	FC
ISO	L-EGD	JASO	FD

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.870
Kinematic viscosity at 40°C	ASTM D445	mm²/s	76.8
Kinematic viscosity at 100°C	ASTM D445	mm²/s	10.4
Viscosity index	ASTM D2270		120
B.N. [HClO4 method]	ASTM D2896	mg KOH/g	1.7
Flash Point COC	ASTM D92	°C	106
Colour	VISUAL		BLACKISH GREEN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

