

WOLF S.T.O.U. 10W40

29/10/2025
1426

This is a semi synthetic lubricant based on carefully selected highly refined base oils for engines, transmissions, wet brakes and hydraulic systems of agricultural tractors.

APPLICATIONS

This oil is recommended for the lubrication of charged and uncharged diesel engines, 4-stroke petrol and LPG engines. This oil is optimized for the lubrication of gearboxes, rear axles, final drives, power take-offs, wet brakes, hydraulic systems of agricultural tractors and off-road equipment.

FEATURES

Anti-wear and oxidation stability: proven protection of critical parts
Cold start: excellent fluidity at low temperature

SPECIFICATIONS

ACEA	E3	NH	NH 410B
AFNOR	NF E 68-603 E	NH	NH 420A
API	CG-4	Sauer Sunstrand/Danfoss	Hydro Static Trans Fluid
API	GL-4	ZF	TE-ML 03A
API	GL-5 (Low speed/high torque)	ZF	TE-ML 05K
API	SF/CE	ZF	TE-ML 06A
DIN	51524 T3 HVLPD	ZF	TE-ML 06B
ALLISON	C4 (Agriculture applic.)	ZF	TE-ML 06C
CASE	MAT 3525	ZF	TE-ML 07B
CASE	MAT 3526	ZF	TE-ML 07D
CASE	MS1207		
CATERPILLAR	TO-2		
DEUTZ	DQC I-02		
EATON VICKERS	I-280-S		
EATON VICKERS	M-2950-S		
FENDT	KDM 17/2012		
FORD	ESN-M2C134 C/D		
FORD	ESN-M2C159 B/C		
FORD	FNH 82009203		
JCB	Standard 4004/6300		
JD	J20C		
JD	J27		
MAN	271		
MB	227.1		
MF	M 1135		
MF	M 1139		
MF	M 1143		
MF	M 1144		
MF	M 1145		
NH	NH 024C		

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.868
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	88.2
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	13.8
Viscosity index	ASTM D2270		160
Pour point	ASTM D6892	°C	-36
CCS viscosity at -25°C	ASTM D5293	mPa.s	6700
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

